

5000 SERIES DISPOSABLE RESPIRATOR
- SINGLE SHIFT USE PARTICLE FILTERING HALF MASK

PRODUCT DATA

1. GENERAL:

1.1	Product Ref.'s	5020V
1.2	Standard	EN 149:2001+A1:2009
1.3	Classification	FFP2 NR

2. PRODUCT DESCRIPTIONS:

- 2.1 5020V Single shift use valved particulate respirator.
- Features exhalation valve to reduce temperature and humidity within the respirator and improve exhalation resistance.

3. PROTECTION:

- 3.1 For protection against non-toxic and low-to-average toxicity solid and liquid aerosols, [e.g. oil-mists], in concentrations up to 10 x WEL, [Workplace Exposure Limit].
i.e. APF, [Assigned Protection Factor] = 10.

4. APPLICATIONS:

- 4.1 Recommended applications include;- pharmaceutical, food processing, agriculture, ship building/repair, powdered chemicals, woodworking industry, construction, metalworking, laboratories, etc..

5. MATERIALS:

5.1	Outer Layer:	Polyester
5.2	Filter Media:	Melt-Blown
5.3	Inner Layer:	Polyester
5.4	Foam:	PVC
5.5	Headstrap:	Knitted Elastic Band
5.6	Exhalation Valve:	Valve Housing - ABS Valve Membrane - Silicon

6. CERTIFICATION:

These particulate respirators are EN149:2001+A1:2009 FFP2 NR certified single-use disposable respirators with CE certification according to European Council Directive 89/686/EEC and subsequent amendments.

EC-Type Examination is certified by INSPEC International Ltd. with the CE notified body number 0194.

Ref.- U5000P2-201412/01

Horizon House, Estate Road Five, Grimsby, DN31 2TG, United Kingdom

• +44 (0)8455 444 000 • sales@betafit.com • www.betafit.com