

5000 SERIES DISPOSABLE RESPIRATOR
- SINGLE SHIFT USE PARTICLE FILTERING HALF MASK

PRODUCT DATA

1. GENERAL:

- | | | |
|-----|----------------|----------------------------|
| 1.1 | Product Ref.'s | 5030V |
| 1.2 | Standard | EN 149:2001+A1:2009 |
| 1.3 | Classification | FFP3 NR |

2. PRODUCT DESCRIPTIONS:

- 2.1 5030V Single shift use valved particulate respirator.
- Features exhalation valve to reduce temperature and humidity within the respirator and improve exhalation resistance.

3. PROTECTION:

- 3.1 For protection against non-toxic, low-to-average toxicity and high toxicity solid and liquid aerosols, [e.g. oil-mists], in concentrations up to 20 x WEL, [Workplace Exposure Limit].
i.e. APF, [Assigned Protection Factor] = 20.

4. APPLICATIONS:

- 4.1 Recommended applications include;- pharmaceutical, welding and soldering, ship building/repair, iron and steel foundries, battery manufacturers, etc..

5. MATERIALS:

- | | | |
|-----|-------------------|---|
| 5.1 | Outer Layer: | Polyester |
| 5.2 | Filter Media: | Melt-Blown |
| 5.3 | Inner Layer: | Polyester |
| 5.4 | Foam: | PVC |
| 5.5 | Headstrap: | Knitted Elastic Band |
| 5.6 | Exhalation Valve: | Valve Housing - ABS
Valve Membrane - Silicon |

6. CERTIFICATION:

These particulate respirators are EN149:2001+A1:2009 FFP3 NR certified single-use disposable respirators with CE certification according to European Council Directive 89/686/EEC and subsequent amendments.

EC-Type Examination is certified by INSPEC International Ltd. with the CE notified body number 0194.

Ref.- U5000P3-201412/01

Horizon House, Estate Road Five, Grimsby, DN31 2TG, United Kingdom
• +44 (0)8455 444 000 • sales@betafit.com • www.betafit.com