

VF RANGE DISPOSABLE RESPIRATOR
- SINGLE SHIFT USE FILTERING HALF MASK
TO PROTECT AGAINST PARTICLES

PRODUCT DATA

1. GENERAL:

1.1	Product Ref.'s	VF-2 VF-2V VF-2CV
1.2	Standard	EN 149:2001+A1:2009
1.3	Classification	FFP2 NR

2. PRODUCT DESCRIPTIONS:

- | | | |
|-----|--------|---|
| 2.1 | VF-2 | Single shift use particulate respirator. |
| 2.2 | VF-2V | Single shift use valved particulate respirator. <ul style="list-style-type: none">• Features exhalation valve to reduce temperature and humidity within the respirator and improve exhalation resistance. |
| 2.3 | VF-2CV | Single shift use valved/charcoal particulate respirator. <ul style="list-style-type: none">• Features exhalation valve, [as VF-2V].• Contains additional pre-filter loaded with activated carbon to protect against nuisance odours and organic vapours BELOW the WEL. |

3. PROTECTION:

- 3.1 For protection against non-toxic and low-to-average toxicity solid and liquid aerosols, [e.g. oil-mists], in concentrations up to 10 x WEL, [Workplace Exposure Limit].
i.e. APF, [Assigned Protection Factor] = 10.

4. APPLICATIONS:

- 4.1 Recommended applications include;- pharmaceutical, food processing, agriculture, ship building/repair, powdered chemicals, woodworking industry, construction, metalworking, laboratories, etc..

VF RANGE DISPOSABLE RESPIRATOR
- SINGLE SHIFT USE FILTERING HALF MASK
TO PROTECT AGAINST PARTICLES

PRODUCT DATA

5. MATERIALS:

5.1	Outer Layer:	Polypropylene
5.2	Filter Media:	High Filtration Efficiency Melt-Blown [Polypropylene]
5.3	Inner Layer:	Polypropylene
5.4	Nosebridge:	Plastic Encapsulated Iron Wire
5.5	Headstrap:	Latex-Free Braided Synthetic Rubber With Polyester Yarn
5.6	Headstrap Buckle:	Polypropylene
5.7	CV Pre-filter:	Active Carbon With Polypropylene Substrate [Note: VF-2CV model only]
5.8	Exhalation Valve:	Valve Housing - Polypropylene Valve Membrane - Synthetic Rubber [Note: VF-2V & VF-2CV models only]

6. DIMENSIONS:

6.1	Respirator:	Width:	114mm
		Height:	163mm
6.2	Nosebridge:		90mm x 5.5mm x 1.3mm [L x W x T]
6.3	Exhalation Valve:		41mm [Diameter] x 11mm [H]
6.4	Headstrap:		700mm x 4.5mm x 1mm [L x W x T]
6.5	Headstrap Buckle:		42mm x 12mm x 2mm [In Arch Shape] [L x W x T]

7. CERTIFICATION:

These particulate respirators are EN149:2001+A1:2009 FFP2 NR certified single-use disposable respirators with CE certification according to European Council Directive 89/686/EEC and subsequent amendments.

EC-Type Examination is certified by BSI [British Standards Institution] with the CE notified body number 0086.