

VF RANGE DISPOSABLE RESPIRATOR
- SINGLE SHIFT USE FILTERING HALF MASK
TO PROTECT AGAINST PARTICLES

PRODUCT DATA

1. GENERAL:

- | | | |
|-----|----------------|----------------------------|
| 1.1 | Product Ref.'s | VF-3V |
| 1.2 | Standard | EN 149:2001+A1:2009 |
| 1.3 | Classification | FFP3 NR |

2. PRODUCT DESCRIPTIONS:

- | | | |
|-----|-------|---|
| 2.1 | VF-3V | Single shift use valved particulate respirator. <ul style="list-style-type: none"> • Features exhalation valve to reduce temperature and humidity within the respirator and improve exhalation resistance. |
|-----|-------|---|

3. PROTECTION:

- | | |
|-----|--|
| 3.1 | For protection against non-toxic, low-to-average toxicity and high toxicity solid and liquid aerosols, [e.g. oil-mists], in concentrations up to 20 x WEL, [Workplace Exposure Limit].
i.e. APF, [Assigned Protection Factor] = 20. |
|-----|--|

4. APPLICATIONS:

- | | |
|-----|--|
| 4.1 | Recommended applications include;- pharmaceutical, welding and soldering, ship building/repair, iron and steel foundries, battery manufacturers, etc.. |
|-----|--|

5. MATERIALS:

- | | | |
|-----|-------------------|--|
| 5.1 | Outer Layer: | Polypropylene |
| 5.2 | Filter Media: | High Filtration Efficiency Melt-Blown [Polypropylene] |
| 5.3 | Inner Layer: | Polypropylene |
| 5.4 | Nosebridge: | Plastic Encapsulated Iron Wire |
| 5.5 | Nose Foam: | Fast Recovery PVC Foam |
| 5.6 | Headstrap: | Latex-Free Braided Synthetic Rubber With Polyester Yarn |
| 5.7 | Headstrap Buckle: | Polypropylene |
| 5.8 | Exhalation Valve: | Valve Housing - Polypropylene
Valve Membrane - Synthetic Rubber |

6. DIMENSIONS:

- | | | | |
|-----|-------------------|---|-------|
| 6.1 | Respirator: | Width: | 123mm |
| | | Height: | 163mm |
| 6.2 | Nosebridge: | 90mm x 5.5mm x 1.3mm [L x W x T] | |
| 6.3 | Nose Foam: | 138.1mm x 22.3mm x 2mm [L x W x T] | |
| 6.4 | Exhalation Valve: | 41mm [Diameter] x 11mm [H] | |
| 6.5 | Headstrap: | 700mm x 4.5mm x 1mm [L x W x T] | |
| 6.6 | Headstrap Buckle: | 42mm x 12mm x 2mm [In Arch Shape] [L x W x T] | |

VF RANGE DISPOSABLE RESPIRATOR
- SINGLE SHIFT USE FILTERING HALF MASK
TO PROTECT AGAINST PARTICLES

PRODUCT DATA

7. CERTIFICATION:

These particulate respirators are EN149:2001+A1:2009 FFP3 NR certified single-use disposable respirators with CE certification according to European Council Directive 89/686/EEC and subsequent amendments.

EC-Type Examination is certified by BSI [British Standards Institution] with the CE notified body number 0086.